HORION MP5APRO

4KUI |Intellegence White Board | Video Conference



M5A Pro Smart Interactive Flat Panel

Horion smart interactive flat panel creates a high-end conference which simplify all the 'six star' function into one device, including projector, electronic whiteboard, computer, display, advertisement player and audio equipment. It is a multipurpose device for conference demonstration, whiteboard writing and annotation, wireless screen mirroring, video conference and remote cooperation, making modern conference easy and efficient.







Voting Machine



Agenda Timer

Smart Wake Up



Feedback



Any Interface Annotation



Welcome Interface

| Wireless Screen Mirroring - Display

4K Screen Mirroring/ Reverse Touch Control/ Quadscreen


- Images of computers, mobile phones and flat panels can be easily displayed on the same screen, and conference display.
- Control the computer in reverse and realize 2-way interaction via Horion screen mirroring device.
- Quad Screen allow to divide into 4 parts for multi screen display from different devices at the same time.

| Video Conference - Collaboration

Whiteboard Sharing / Writing Synchronization / HD Video Conference

With unique cloud conference system, smartphones, tablets, computers and interactive flat panels can be accessed for real-time. stable face-to-face communication, sharing and collaboration.





Touch Handwriting



Palm Erase

| Touch Handwriting - Creating

Pen Writing / Smart Form / Automatic Recognition

Real writing experience with 1mm recognition accuracy, 20-point touch control, new writing software, single and multi point writing mode, brush selection and smart handwriting algorithm.

Also, M5Pro able to search keywords with one click away with default search engine while connecting to the network. Through bluetooth function, it can connect to wireless devices for data transmission and document printing.

| Horion Conference Management

Smart Centralized Control System / Conference Doorplate/ Enterprise Cloud

Smart Centralized Control System:

It can control multiple interactive flat panels at the same time, which offers information contribution and conference management.


Conference Doorplate:


It supports conference information display, demand submission (completing the use of the conference room, preparing tea, etc.)

Enterprise Cloud:

It supports whiteboard writing and document PPT one-key saving, providing storage space for important conference documents of enterprise.

Supportive Devices





Specification of M5A Pro Interactive Flat Panel

	М	5A Pro	
Model	65M5A Pro	75M5A Pro	86M5A Pro
Screen Size	65"	75"	86"
Display			
acklight type		D-LED	
esolutions	3840*2180 (UHD)		
rightness	350 cd/m ²		
creen Contrast Ratio	1200:1		
esponse Time	8ms		
rixel Distance	0.372mm*0.372mm	0.4296mm*0.4296mm	0.4935mm*0.4935mm
rame Rate		60Hz	
erspective		178*(H)/178*(V)	
Color Saturation (x%NTSC)		72%	
isible Area	1429.48mm*803.52mm	1549.664mm*927.936mm	1895.04mm*1065.96mm
Colorfulness		1.07B (10bit)	
ife		30,000 hrs	
ystem Properties			
ystem Version	Android 11.0 (Optional computer module for Windows system)		
PU Model	ARM A73		
PU Working Frequency	1.8GHz		
lumber of CPU cores	Four		
PU	Mali-G52		
nternal Cache Capacity* (RAM)	8GB		
nternal Storage Capacity (ROM)	64GB Standard		
ower Parameters			
oltage	100V-240V/AC, 50/60Hz		
faximum Power (without OPS)	220W	300W	380W
tandby Power		<0.5W	
ower (AC) Input		*1	
ouch Parameters			
ouch Screen	Touch specification: infrared touch box; Gla	uss specification:3.2mmAG toughened glass; Re	sponse time: ≤8ms; Touch accuracy: ±1mm
Camera + Microphone			
Camera	Pixel: 1,300W		
4icrophone	Linear 8-array microphone; Audio pickup distance: 8m		
	Lin	ear o-array microphone, Addio pickup distance.	OIII
unction			
ssociated Power	10W*2		
IFC	Support		
luetooth		Support	
Display Interface			
lumber of Interfaces	HDMI port*2, DP port*1, VGA input port*1, OPS port*1, Touch-USB 2.0*1, Public USB*2, LAN port*1, Android USB*2, PC-Audio input port*1, S/PDIF output port*1, Audio OUT*1, RS232*1		
Structure	1 3 Addion	parpart 17 on on output port 1, Audio Oot	
let Weight	42Kg±1.5Kg	50Kg±1.5Kg	68Kg±1.5Kg
Gross Weight	54Kg±1.5Kg (heavy carton)	70Kg±1.5Kg (heavy carton)	89Kg±1.5Kg (heavy carton)
are Machine Dimensions (L*W*H)	1511.56mm*86.08mm*907.89mm	1722.41mm*87.08mm*1022.15mm	1967.65mm*87.28mm*1160.15mm
ackage Size (L*W*H)	1,660mm*245mm*1,045mm (heacy carton)	1,880mm*280mm*1,160mm (heavy carton)	2,140mm*280mm*1,340mm (heavy carto
ESA Hole Location	4-MB screw hole 600mm*400mm	4-MB screw hole 800mm*400mm	4-MB screw hole 800mm*600mm
hell Material (face frame/ rear shell)			
hell Color (face frame / rear shell)		Dark Tarnish / Black	
Computer Module (Optional)			
5.OS (optional)	In	tel*CoreTMi5 processor, RAM: 8GB + SSD: 1280	SB.
	"	1280 TOTAL TITLE PROCESSOR, NAME 1. 000 + 330. 1280	
acking List			
ist		ole-ended Writing Pen*1, Remote Control*1, Exp Certificate/Warranty Card*1, 3m Power Cord*1	
Wilson San V V V		25. mouto warranty out 1, on Fower cold 1	

^{**}Note: The relevant data are for reference only. The specofic parameters shall be subject to the actual product. The data were carefully checked for accuracy. There's no notice of any change in product function and specification, and the company reserves the final interpretation right to the relevant contents in the data.